

I. AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

1.-2. (Canceled)

3. (Presently amended) A loudspeaker system comprising:

a loudspeaker having a loudspeaker housing;

Aa mounting mechanism for mounting a the loudspeaker housing to a structure,
comprising: where the mounting mechanism includes:

a shaft for coupling the mounting mechanism to the loudspeaker housing;

an arm member movably coupled to the shaft and adjustable generally along a mounting direction; and

an interface section, where the arm member is pivotably coupled to the interface section for rotation about an axis is generally orthogonal to the mounting direction, the arm member pivotally rotatable independent of any movement of the shaft, and the interface section is movably coupled to the shaft and adjustable generally along the mounting direction.

4. (Canceled)

5. (Presently amended) The ~~mounting mechanism~~-loudspeaker system of claim 3 where the shaft threadedly engages the interface section and a position of the arm member and interface section is adjustable generally along the mounting direction through rotation of the shaft.

6. (Presently amended) The ~~mounting mechanism~~-loudspeaker system of claim 3 where the interface section has a bore and the shaft is disposed in the bore.

7. (Presently amended) The ~~mounting mechanism~~-loudspeaker system of claim 6 where the shaft movably engages the bore for adjusting a position of the mounting mechanism relative to the loudspeaker housing.

8. (Presently amended) The ~~mounting mechanism~~-loudspeaker system of claim 3 where the arm member comprises a base section and the interface section is disposed in the base section.

9. (Presently amended) The ~~mounting mechanism~~-loudspeaker system of claim 3 comprising a spring mechanism interconnecting the arm member and the interface section for biasing the arm member into engagement with the structure.

10. (Presently amended) The ~~mounting mechanism~~-loudspeaker system of claim 3 comprising a spring mechanism contacting the arm member for biasing the arm member into engagement with the structure.

11. (Presently amended) The ~~mounting mechanism~~-loudspeaker system of claim 3 where the arm member comprises an attachment edge for engaging the structure.

12. (Presently amended) The ~~mounting mechanism~~-loudspeaker system of claim 11 where the attachment edge comprises a toothed surface.

13. (Presently amended) A ~~mounting mechanism~~-loudspeaker system for mounting a housing to a structure, comprising:

a loudspeaker having a loudspeaker housing;

a mounting mechanism for mounting the loudspeaker housing to a structure;

a shaft for coupling the mounting mechanism to the loudspeaker housing;

an interface section, where the shaft is movably coupled to the interface section for adjusting a position of the mounting mechanism relative to the loudspeaker housing;

a pivotable arm member for engaging the structure, the arm member pivotably coupled to the interface section for rotation about an axis generally orthogonal to the mounting direction, the arm member coupled to the shaft whereby the arm member is pivotally rotatable independent of any movement of the shaft; and

a spring mechanism contacting the arm member for biasing the arm member into engagement with the structure.

14. (Presently amended) The ~~mounting mechanism~~-loudspeaker system of claim 13 where the arm member is movably coupled to the shaft for adjusting a position of the arm member relative to the loudspeaker housing.

15. (Cancelled)

16. (Cancelled)

17. (Presently amended) The ~~mounting mechanism~~-loudspeaker system of claim 13 where the shaft threadedly engages the interface section and the position of the mounting mechanism is adjustable through rotation of the shaft.

18. (Presently amended) The ~~mounting mechanism~~-loudspeaker system of claim 13 where the interface section has a bore and the shaft is disposed in the bore.

19. (Presently amended) The ~~mounting mechanism~~-loudspeaker system of claim 18 where the shaft movably engages the bore for adjusting a position of the mounting mechanism relative to the loudspeaker housing.

20. (Presently amended) The ~~mounting mechanism~~-loudspeaker system of claim 13 where the arm member comprises a base section and the interface section is disposed in the base section.

21. (Presently amended) The ~~mounting mechanism~~ loudspeaker system of claim 13 where the arm member comprises an attachment edge for engaging the structure.

22. (Presently amended) The ~~mounting mechanism~~ loudspeaker system of claim 21 where the attachment edge comprises a toothed surface.

23. (Presently amended) A ~~mounting assembly for mounting in an opening of a structure,~~ loudspeaker system comprising:

a loudspeaker;

a loudspeaker housing adapted for insertion into ~~the~~ an opening of a structure along a mounting direction;

a mounting assembly for mounting the loudspeaker housing in the opening;

a mounting mechanism coupled to the loudspeaker housing and including an arm member pivotable between a first position and a second position, where at the first position the arm member enables insertion of the loudspeaker housing in the opening, and at the second position the arm member extends generally away from the loudspeaker housing into engagement with a surface of the structure defining the opening;

a spring mechanism connected to the arm member for biasing the arm member toward the second position; and

a shaft interconnecting the mounting mechanism and the loudspeaker housing, whereby the arm member of the mounting mechanism is pivotal between the first position and the second position independent of any movement of the shaft.

24. (Cancelled).

25. (Presently amended) The ~~mounting assembly~~ loudspeaker system of claim 23 where the mounting mechanism is movably coupled to the shaft for adjusting a position of the arm member relative to the loudspeaker housing along the mounting direction.

26. (Presently amended) The ~~mounting assembly~~ loudspeaker system of claim 25 where the mounting mechanism comprises an interface section movably coupled to the shaft and the arm member is pivotably coupled to the interface section.

27. (Withdrawn) A method for mounting a housing assembly to a structure including a side edge defining an opening, the method comprising:

providing the housing assembly with a housing and an arm member coupled to the housing, the arm member movable between an open position at which the arm member extends generally away from the housing beyond the side edge and a closed position at which the arm member is retracted generally toward the housing;

inserting the housing assembly into the opening, where the arm member contacts the side edge and moves toward the closed position; and

continuing to insert the housing assembly into the opening until the arm member clears the side edge and moves toward the open position, where at least a portion of the arm member is disposed adjacent to a back side of the structure to prevent removal of the housing assembly from the opening while the arm member is in the open position.

28. (Withdrawn) The method of claim 27 where the housing assembly is a part of a loudspeaker assembly.

29. (Withdrawn) The method of claim 27 where inserting the housing comprises inserting along a mounting direction, and movement of the arm member between the open and

closed positions translates the arm member portion generally along a lateral direction orthogonal to the mounting direction.

30. (Withdrawn) The method of claim 27 where contact of the arm member with the side edge forces the arm member to move toward the closed position in opposition to a biasing force impressed by a spring connected to the arm member, and movement of the arm member toward the open position is assisted by the spring force.

31. (Withdrawn) The method of claim 27 comprising, after the arm member portion is disposed adjacent to the back side of the structure, adjusting a position of the arm member relative to the housing to cause the arm member portion to abut the back side.

32. (Withdrawn) The method of claim 31 where the arm member is movably coupled to the housing through a shaft, and adjusting the position of the arm member comprises moving the arm member relative to the shaft.

33. (Withdrawn) The method of claim 31 where the arm member is pivotably coupled to an interface section and a threaded shaft is mounted to the housing and mated to threads of the interface section, and adjusting the position of the arm member comprises turning the shaft.

34. (Presently amended) A ~~mounting assembly for mounting a housing to a structure,~~
loudspeaker system comprising: ~~a housing;~~

a loudspeaker housing;

a shaft; and

a mounting mechanism movably coupled to the shaft and adjustable generally along a mounting direction relative to the loudspeaker housing, arm member and an interface section,

the arm member pivotably coupled to the interface section for rotation about an axis generally orthogonal to the mounting direction.

35. (Presently amended) The ~~mounting assembly~~-loudspeaker system of claim 34 where the interface section is movably coupled to the shaft and adjustable generally along the mounting direction.

36. (Presently amended) The ~~mounting assembly~~-loudspeaker system of claim 35 where the shaft threadedly engages the interface section and a position of the arm member and interface section is adjustable generally along the mounting direction through rotation of the shaft.

37. (Presently amended) The ~~mounting assembly~~-loudspeaker system of claim 35 where the interface section has a bore and shaft is disposed in the bore.

38. (Presently amended) The ~~mounting assembly~~-loudspeaker system of claim 37 where the shaft movably engages the bore for adjusting a position of the mounting mechanism relative to the loudspeaker housing.

39. (Presently amended) The ~~mounting assembly~~-loudspeaker system of claim 35 where the arm member comprises a base section and the interface section is disposed in the base section.

40. (Presently amended) The ~~mounting assembly~~-loudspeaker system of claim 35 comprising a spring mechanism interconnecting the arm member and the interface section for biasing the arm member into engagement with the structure.

41. (Presently amended) The ~~mounting assembly~~-loudspeaker system of claim 34 comprising a spring mechanism contacting the arm member for biasing the arm member into engagement with the structure.

42. (Presently amended) The ~~mounting assembly~~ loudspeaker system of claim 34 where the arm member comprises an attachment edge for engaging the structure.

43. (Presently amended) The ~~mounting assembly~~ loudspeaker system of claim 42 where the attachment edge comprises a toothed surface.